

TRUSS TO WALL  
CONNECTION  
BY ROOF TRUSS MFG.

TRUSS BOTTOM CHORD,  
(N.I.C.)

TOP TRACK

3/4" MAX.

LOAD BEARING WALL STUDS

BEARING TOLERANCE

ROOF TRUSS  
@ 48" O.C. (N.I.C.)

NOTE:  
SPLICE TOP TRACK AT  
DOUBLE STUD LOCATIONS  
ONLY.

CONTINUOUS TOP  
TRACK.

1/8" 1-12

ALTERNATE DOUBLE  
STUD ATTACHMENT

(1) #10-16 SCREW  
@ EACH FLANGE


STEEL STUDS BETWEEN  
ROOF TRUSSES.

CONNECTION BY  
ROOF TRUSS MFG.  
ATTACH DIRECTLY  
TO WALL STUD

DOUBLE STUDS TO ALIGN  
BELOW EA. ROOF TRUSS

(2) #10-16 SCREWS  
@ 12" O.C.

TELLING™



**BUILDSTRONG**

6272 CENTER STREET  
MENTOR, OHIO 44060  
PHONE: 440-974-3370

DETAIL IS FOR  
REFERENCE ONLY.  
NOT FOR CONSTRUCTION.

DETAIL PROVIDED BY:



100 CAMELOT DRIVE  
FOND DU LAC, WI 54935  
PHONE: (920) 926-9800

# TRUSS BEARING DETAIL