

FOR SOLID BLOCKING:
 NOTCH AND BEND UP TRACK
 FLANGES 90° OR ANCHOR
 BLOCKING TO VERTICALS
 W/ CLIP L's

STEEL STUDS

SOLID BLOCKING @
 10'-0" O.C. AND AT
 WALL OPENINGS OR
 CORNERS

(1) #10-16 SCREW
 @ EACH STUD

CONTINUOUS 1 1/2" x 18 GA.
 FLAT STRAPPING ATTACHED
 TO BOTH FLANGES

ATTACH STRAPPING TO
 BLOCKING W/ (4) #10-16
 EACH FACE

STRAP & BLOCK BRIDGING
 MAY BE USED WITH ALL
 STUD DEPTHS, CURVED OR
 STRAIGHT WALLS.

TELLING™

BUILDSTRONG
 6272 CENTER STREET
 MENTOR, OHIO 44060
 PHONE: 440-974-3370

DETAIL IS FOR
 REFERENCE ONLY.
 NOT FOR CONSTRUCTION.

DETAIL PROVIDED BY:

EXCEL
 ENGINEERING, LLC

100 CAMELOT DRIVE
 FOND DU LAC, WI 54935
 PHONE: (920) 926-9800

STRAP & BLOCK LOAD BEARING WALL BRIDGING