

VERTICAL SLIDE CLIP  
INSTALL PER MFG.  
SPECIFICATIONS.

@ JAMB CONDITIONS:  
PROVIDE (1) SLIDE CLIP  
@ EA. SIDE OF JAMB  
(2) V.S.C. PER JAMB

STRUCTURAL STL.  
BEAM (N.I.C.)


STEEL STUDS  
REFER TO SECTIONS

(2) 0.145"Ø P.D.F.'S  
@ EACH SLIDE CLIP  
MAINTAIN 1" MIN.  
FASTENER SPACING &  
1/2" MIN. EDGE DIST.

PROJECT ENGINEER TO VERIFY  
ALL CONNECTION TO BOTTOM  
FLANGE OF STEEL BEAMS

CONNECTION TO OCCUR  
6" MIN. FROM PUNCHOUT.  
FOR PUNCHOUT REINFORCING

TELLING™



BUILDSTRONG

6272 CENTER STREET  
MENTOR, OHIO 44060  
PHONE: 440-974-3370

DETAIL IS FOR  
REFERENCE ONLY.  
NOT FOR CONSTRUCTION.

DETAIL PROVIDED BY:



100 CAMELOT DRIVE  
FOND DU LAC, WI 54935  
PHONE: (920) 926-9800

TYPICAL BYPASS @ BEAM

VERTICAL SLIDE CLIP DETAIL